



Dinami Series Safes

Grades I-II-III-IV-V · Standard EN 1143-1



History

Ferrimax, is a leading Spanish company producing security products to the highest safety standards. With more than 30 years experience in the security sector and many blue chip customers, Banks, Jewellers, Retailers and service stations all look to Ferrimax for top quality products.

Grade III: optional combination lock



The Spanish Association for Standardization and Certification (AENOR) certifies that the quality management system adopted by Ferrimax, s.a. for the design, the manufacturing, the commercialisation, the after sales service and maintenance of safes and physical security products, complies with the requirements of the Standard EN ISO 9001:2000.



Dinami Series Safes

Grades I-II-III-IV-V · Standard UNE 1143-1

New series

In Greek Dinami means resistance or stamina - a fitting name for this new product range developed by Ferrimax to resist the sophisticated new methods of attack used by today's criminals.

Quality

All Ferrimax's manufacturing processes conform to ISO 9001:2000.

Sustainable

The whole manufacturing cycle from the raw materials to the final packaging are geared towards the production of the environment.

Tested and certificated

The Dinami series has been designed and manufactured to the European testing standards for safes UNE 1143-1.

All tests were undertaken by the German Laboratory VdS and the French Laboratory C.N.P.P. The process has been certified by VdS and a2p.

Technical features

A new generation of composite materials based on "DSP" (Densified System Particules) has reduced the weight by approximately 30% but still conforms to the required security grade standard EN 1143-1.

The wallthickness is 60 mm for grades I-II-III-IV and 80 mm for grade V.

The door thickness, including the chamber, is 130 mm for grades I-II-III-IV and 150 mm for grade V.

All the safes are finished in Ferrimax grey - RAL 7040.

Protection

The sensitive locking zones, the bolts, relocking system and main key lock have anti drilling protection fitted as standard.

The key lock is also protected by a tempered glass security plate and re-locker system.

To resist attack to the hinges a full door height rebate rail is fitted whilst the leading edge of the doors are secured by multiple 30 mm diameter bolts*.

**Varies according to model*

Dinami Series Safes range



[Dinami 680]



[Dinami 650]



[Dinami 625]

Locks and re-locking systems



- GRADES I and II: one double-bit key lock class A EN1300
- GRADE III: one double-bit key lock class B EN1300
- GRADES IV and V: one double-bit key + one mechanical combination lock, both class B EN1300

All the models of the Dinami series safes are protected with re-locking systems as standard.

Options

As an option, Dinami series safes can be provided with:

- an internal cupboard with key
- a mechanical combination lock
- a electronic combination lock

Ferrimax can also include other options to match individual clients requirements.



Deposit systems

Dinami safes 602, with a deposit drawer.

Special product without certification.



[Dinami 618]

[Dinami 616]

[Dinami 612]

[Dinami 610]

[Dinami 602]

